

AMC PACER PACER V8 (1978-1980)

**ENGINE**

Capacity: 4,7 liter, Filter capacity: 0,95 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Racing Oil 15W-50	Classic Monograde 50	

Change every 12000 km/ 8 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Multigrade 15W-40	Classic Multigrade 10W-30	Classic Monograde 30

Change every 12000 km/ 8 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
HDX 10W		

Change every 12000 km/ 8 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Racing Oil 15W-50	Classic Monograde 50	

Change every 6000 km/ 8 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Multigrade 15W-40	Classic Multigrade 10W-30	Classic Monograde 30

Change every 6000 km/ 8 months

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1		
HDX 10W		

Change every 6000 km/ 8 months

AMC PACER PACER V8 (1978-1980)

**DIFFERENTIAL REAR**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

Check every 12000 km/ 8 months, change every 48000 km/ 30 months

DIFFERENTIAL REAR LIMITED-SLIP Twin-Grip

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90

Check every 12000 km/ 8 months, change every 48000 km/ 30 months

TRANSMISSION AUTOMATIC 3/1

Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A

Check every 12000 km/ 8 months, change every 48000 km/ 30 months

TRANSMISSION MANUAL 4/1

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 12000 km/ 8 months, change every 48000 km/ 30 months

TRANSMISSION MANUAL + OVERDRIVE 4/1

Capacity: 1,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

AMC PACER PACER V8 (1978-1980)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 12000 km/ 8 months

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

Check every 12000 km/ 8 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12000 km/ 8 months

COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12000 km/ 8 months, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.