ASTON MARTIN DB4 DB4 VANTAGE (1962-1963)



ENGINE Capacity: 9,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Change every 4000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 4000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 4000 km/ 6 months		
DIFFERENTIAL REAR Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check every 4000 km/6 months, change	every 16000 km/ 18 months	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	
Check every 4000 km/ 6 months, change	every 16000 km/ 18 months	

ASTON MARTIN DB4 DB4 VANTAGE (1962-1963)



USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Check every 4000 km/ 6 months, change every 16000 km/ 1	8 months
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 50	
Check every 4000 km/ 6 months, change every 16000 km/ 1	8 months
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES PROP	ELLER SHAFT JOINTS	

EL BEARINGS FRONT	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ASTON MARTIN DB4 DB4 VANTAGE (1962-1963)



GREASE POINTS/NIPPLES WHEEL BE	ARINGS REAR	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 15,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.