

# AUDI (EU) 60/72/75/80/90 F103 60 (48 KW)

## EXPORT (1968-1972)

**ENGINE**

Capacity: 4 liter

USE	CLIMATE
Normal	Tropical

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 20W-50***Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Racing Oil 15W-50**

## PRODUCT RECOMMENDATION 2

**Classic Multigrade 15W-40**

## PRODUCT RECOMMENDATION 3

**Classic Multigrade 10W-30***Change every 10000 km/ 6 months*

USE	CLIMATE
Initial service	Tropical

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 20W-50***Change every 500 km*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Racing Oil 15W-50**

## PRODUCT RECOMMENDATION 2

**Classic Multigrade 15W-40**

## PRODUCT RECOMMENDATION 3

**Classic Multigrade 10W-30***Change every 500 km*

USE	CLIMATE
Second change only	Tropical

## PRODUCT RECOMMENDATION 1

**Classic Multigrade 20W-50***Change every 5000 km*

USE	CLIMATE
Second change only	Moderate

## PRODUCT RECOMMENDATION 1

**Classic Racing Oil 15W-50**

## PRODUCT RECOMMENDATION 2

**Classic Multigrade 15W-40**

## PRODUCT RECOMMENDATION 3

**Classic Multigrade 10W-30***Change every 5000 km*

# AUDI (EU) 60/72/75/80/90 F103 60 (48 KW) EXPORT (1968-1972)

**TRANSAXLE MANUAL 4/1**

Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 80</b>		

*Check every 10000 km, change every 30000 km*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic Gear EP 80</b>		

*Change every 500 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

**WHEEL BEARINGS**

Capacity: 10 grams

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 10000 km/ 6 months***COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.