AUDI (EU) 80 80/82 (B1) 80 GT (1973-1975)



ENGINE Capacity: 4 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1 Classic Monograde 50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 7500 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 7500 km/ 6 months		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 1000 km		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 1000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Oh		

Change every 1000 km

AUDI (EU) 80 80/82 (B1) 80 GT (1973-1975)



TRANSAXLE MANUAL 4/1 Capacity: 1,8 liter (Dry fill), Capacity: 1,6 lit	r (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Observes success 0.4 manufility	

Change every 24 months

WHEEL BEARINGS Capacity: 10 grams		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 12 months

COOLING SYSTEM Capacity: 6,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.