AUSTIN A35 A35 (1956-1962)



ENGINE Capacity: 3,98 liter, Filter capacity: 0,57 liter		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Change every 3000 km		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 3000 km		

DIFFERENTIAL Capacity: 1 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 1500 km, change every	9000 km	
USE	CLIMATE	
Normal	Arctic	
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 1500 km, change every	9000 km	

TRANSMISSION MANUAL 4/1 Capacity: 1,33 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 10W-30	Classic Monograde 30		
Check every 1500 km, change every 9000 km			

AUSTIN A35 A35 (1956-1962)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 1500 km	

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		
Change every 9000 km		

COOLING SYSTEM Capacity: 5,4 liter (+ heater), Capacity: 4,93 liter (Without heater)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

STEERING BOX		
USE	CL	IMATE
Normal	M	loderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
USE	CL	IMATE
Normal	Aı	rctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.