AUSTIN MAXI ADO14 MAXI 2 1750HL (1980-1981)



| ENGINE/TRANSAXLE MANUAL Capacity: 5,6 liter, Filter capacity: 0,6 liter | | |
|--|---------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Multigrade 20W-50 | | |
| Change every 10000 km/ 6 months | | · · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Classic Racing Oil 15W-50 | Classic Multigrade 15W-40 | |
| Change every 10000 km/ 6 months | | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Multigrade 10W-30 | | |
| Change every 10000 km/ 6 months | | |
| | | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| | | |

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

| HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|---|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| Check every 10000 km/ 6 months, change every 30000 km/ 18 months | | |

AUSTIN MAXI ADO14 MAXI 2 1750HL (1980-1981)



| GREASE POINTS/NIPPLES | | |
|------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

| COOLING SYSTEM Capacity: 5,2 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check every 10000 km/ 6 months | | |

| CARBURETTOR DAMPER | |
|--------------------------------|---------------|
| USE | CLIMATE |
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Classic Multigrade 20W-50 | |
| Check every 10000 km/ 6 months | |

| USE | | CLIMATE |
|---------------------------|---------------------------|---------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Racing Oil 15W-50 | Classic Multigrade 15W-40 | Classic Multigrade 10W-30 |

Check every 10000 km/ 6 months

| STEERING BOX | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear MP 90 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.