AUSTIN MAXI ADO14 MAXI 2 1750HLS (1980-1981)



ENGINE/TRANSAXLE MANUAL Capacity: 5,6 liter, Filter capacity: 0,6 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Change every 10000 km/ 6 months		
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 10000 km/ 6 months, change every 30000 km/ 18	3 months

Drauliquid DOT 3

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

AUSTIN MAXI ADO14 MAXI 2 1750HLS (1980-1981)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 5,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
01 1 100001 10 11		I

Check every 10000 km/6 months

CARBURETTOR DAMPER		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Check every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

Classic Multigrade 15W-40

Classic Racing Oil 15W-50
Check every 10000 km/ 6 months

STEERING BOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Classic Multigrade 10W-30