

# AUSTIN MINI AD015 MINI 850 MK I (1964-1967)



## ENGINE/TRANSAXLE MANUAL

Capacity: 4,8 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Classic Multigrade 20W-50***Change every 10000 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30***Change every 10000 km*

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 5000 km*

## HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Check every 5000 km*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 5000 km*

# AUSTIN MINI AD015 MINI 850 MK I (1964-1967)



## COOLING SYSTEM

Capacity: 3,55 liter (+ heater), Capacity: 3 liter (Without heater)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

## CARBURETTOR DAMPER

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.