AUTOBIANCHI A112 A112 ELEGANT (1977-1982)



ENGINE A112B1.000		
Capacity: 3,9 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1 Classic Monograde 50		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 10000 km/ 6 months	,	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 10000 km/6 months		
USE		CLIMATE · ·
Severe		Tropical
PRODUCT RECOMMENDATION 1 Classic Monograde 50		
_		
Change every 5000 km/ 3 months		OI IMATE
use Severe		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 5000 km/ 3 months		
USE		CLIMATE
Severe		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 5000 km/ 3 months		

AUTOBIANCHI A112 A112 ELEGANT (1977-1982)



TRANSAXLE FRONT 4/1 Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear ZC 90	
Check every 10000 km, change every 30000 km	·

TRANSAXLE FRONT 5/1 Capacity: 2,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear ZC 90		
Check every 10000 km, change every 30000 km		

Capacity: 0,33 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

COOLING SYSTEM Capacity: 5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Change every 60000 km/24 months

STEERING BOX Capacity: 0,14 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.