BMW (EU) 1500, 1600, 1800, 2000 E8 1800 (1963-1968)



ENGINE Capacity: 4,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Change every 3000 km		·
USE		CLIMATE
Summer months		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Change every 6000 km	·	

DIFFERENTIAL REAR Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 12000 km, change every 24000 km	

TRANSMISSION AUTOMATIC 3/1 Capacity: 2 liter (Refill), Capacity: 5 liter (Tensor)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF A	

TRANSMISSION MANUAL 4/1 Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 12000 km, change every 240	km	

BMW (EU) 1500, 1600, 1800, 2000 E8 1800 (1963-1968)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 3000 km		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Ot against the second of the s		

Change every 60000 km

COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX Capacity: 0,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 12000 km	·

Check every 12000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.