

BMW (EU) 6 SERIES E24 635 CSI (1978-1982)**ENGINE M30B35**

Capacity: 6,5 liter (+ oil cooler), Filter capacity: 0,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 7500 km*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 20W-50

PRODUCT RECOMMENDATION 3

Classic Multigrade 15W-40*Change every 7500 km***DIFFERENTIAL REAR**

Capacity: 1,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 15000 km, change every 30000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 15000 km, change every 30000 km***TRANSMISSION MANUAL** Getrag 260 5/1

Capacity: 1,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 15000 km, change every 30000 km*

BMW (EU) 6 SERIES E24 635 CSI (1978-1982)**HYDRAULIC SYSTEM LEVELLING**

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| LHM + | | |

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-S DOT 4 | | |

Check every 7500 km, change every 12 months

POWER STEERING SEPARATE SYSTEM

Capacity: 1,2 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic ATF A | | |

Check every 7500 km

COOLING SYSTEM

Capacity: 12 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.