

BMW (EU) 6 SERIES E24 635 CSI (1982-1987)**ENGINE M30B35**

Capacity: 6,5 liter (+ oil cooler), Capacity: 5,75 liter (Service fill), Filter capacity: 0,75 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 7500 km*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 20W-50

PRODUCT RECOMMENDATION 3

Classic Multigrade 15W-40*Change every 7500 km***DIFFERENTIAL REAR**

Capacity: 1,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 15000 km, change every 30000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 15000 km, change every 30000 km***TRANSMISSION AUTOMATIC 3/1**

Capacity: 2 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 15000 km, change every 30000 km*

BMW (EU) 6 SERIES E24 635 CSI (1982-1987)**TRANSMISSION MANUAL** Getrag 260 5/1

Capacity: 1,3 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear EP 80 | | |

*Check every 15000 km, change every 30000 km***TRANSMISSION MANUAL** Getrag 265 5/1

Capacity: 1,5-1,7 liter

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear EP 80 | | |

HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-S DOT 4 | | |

*Check every 7500 km, change every 12 months***POWER STEERING SEPARATE SYSTEM**

Capacity: 2 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic ATF A | | |

*Check every 7500 km***COOLING SYSTEM**

Capacity: 12 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.