BMW (EU) 700, LS 700 CS (1963-1965)



ENGINE Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
	•	

Change every 3000 km

Check every 6000 km

TRANSAXLE 4/1 Capacity: 1,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Chook ayon, 6000 km, ahanga ayon, 19000 km	·

Check every 6000 km, change every 18000 km

HYDRAULIC BRAKE SYSTEM		
CLIMATE		
Moderate		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 3000 km	,	

SUSPENSION FRONT Capacity: 0,01 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Check every 3000 km	

PRODUCT RECOMMENDATION

BMW (EU) 700, LS 700 CS (1963-1965)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.