CADILLAC (USA / CAN) ELDORADO ELDORADO (1970-1975)



ENGINE Capacity: 5,7 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 10000 km/ 4 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 15W-40	Classic Multigrade 10W-30	
Change every 10000 km/ 4 months		

DIFFERENTIAL FRONT Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 6 months	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Check every 6 months	·

DIFFERENTIAL FRONT LIMITED SLIP Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear LS 90	
Check every 6 months	

CADILLAC (USA / CAN) ELDORADO ELDORADO (1970-1975)



TRANSMISSION AUTOMATIC Turbo-Hydramatic THM400 3/1 Capacity: 5,2 liter (Refill)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Classic ATF A			
Check every 10000 km/ 4 months, change every 36000 km/ 24	months		

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 10000 km/ 4 months	

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF Almirol	
Check every 10000 km/ 4 months		·

COOLING SYSTEM Capacity: 19,2 liter, Capacity: 19,4 liter (+ airconditioning)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10000 km/ 4 months, cl	hange every 36000 km/ 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo