

DAF 44 44 (1970-1974)



ENGINE 844 Capacity: 2 liter		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Classic Racing Oil 15W-50	PRODUCT RECOMMENDATION 2 Classic Multigrade 20W-50	PRODUCT RECOMMENDATION 3 Classic Multigrade 15W-40

Change every 5000 km/ 3 months

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Classic Multigrade 10W-30		

Change every 5000 km/ 3 months

FINAL DRIVES Capacity: 250 CM3 (each)		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Classic Gear MP 90	PRODUCT RECOMMENDATION 2 Classic Gear EP 80	

Change every 20000 km

POWER DIVIDER 1/1 Capacity: 475 CM3		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Classic Gear MP 90	PRODUCT RECOMMENDATION 2 Classic Gear EP 80	

Change every 20000 km

HYDRAULIC BRAKE SYSTEM		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 Drauliquid DOT 3		

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.