

**DAF 600 / 750 / DAFFODIL 750 (1961-1963)**

**ENGINE 746**  
Capacity: 2 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Classic Multigrade 15W-40</b>	<b>Classic Monograde 30</b>	

*Change every 3000 km/ 3 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic Multigrade 10W-30</b>		

*Change every 3000 km/ 3 months*

**FINAL DRIVES**  
Capacity: 150 CM3 (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

**POWER DIVIDER 1/1**  
Capacity: 425 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

**VARIOMATIC TRANSMISSION PRIMARY DISC**  
Capacity: 75 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

**DAF 600 / 750 / DAFFODIL 750 (1961-1963)****VARIOMATIC TRANSMISSION SECONDARY DISC**

Capacity: 75 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Classic ATF A</b>		

**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Change every 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*