

DATSUN (NISSAN) SKYLINE C10/C110 240K GT GC110 (1972-1977)



ENGINE L24
Capacity: 5,7 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Change every 5000 km

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

Change every 5000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 3

Classic Monograde 30

Change every 5000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W

Change every 5000 km

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Change every 1000 km

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

Change every 1000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 3

Classic Monograde 30

Change every 1000 km

DATSUN (NISSAN) SKYLINE C10/C110 240K GT GC110 (1972-1977)



USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
<i>Change every 1000 km</i>		

REAR AXLE Capacity: 1 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 50000 km</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Gearlube RPC 75W-80	SP Gear 5015
<i>Change every 50000 km</i>		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		
<i>Change every 1000 km</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Gearlube RPC 75W-80	SP Gear 5015
<i>Change every 1000 km</i>		



DATSUN (NISSAN) SKYLINE C10/C110 240K GT GC110 (1972-1977)

**TRANSMISSION 4/1 4/1**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 50000 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 50000 km*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 1000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 1000 km***TRANSMISSION AUTOMATIC 3/1**

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 5000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 20000 km*

DATSUN (NISSAN) SKYLINE C10/C110 240K GT GC110 (1972-1977)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Change every 20000 km</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 50000 km</i>		

WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 50000 km</i>		

COOLING SYSTEM

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Change every 40000 km</i>		

DATSUN (NISSAN) SKYLINE C10/C110 240K GT GC110 (1972-1977)

**STEERING GEAR**

Capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 5000 km*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 5000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.