

FIAT (EU) 126 126 0.65 126A1 (1977-1982)**ENGINE 126A1.000**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Check every 500 km, change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Check every 500 km, change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Check every 500 km, change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Check every 500 km, change every 10000 km/ 6 months***TRANSAXLE MANUAL 4/1**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear ZC 90*Check every 10000 km, change every 30000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

FIAT (EU) 126 126 0.65 126A1 (1977-1982)**GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Labora Grease		

Change every 30000 km

STEERING BOX

Capacity: 0,12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.