Check every 500 km, change every 2500 km

FIAT (EU) 500 NUOVA 500 D (1960-1965)



ENGINE Capacity: 1,75 liter				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Classic Multigrade 15W-40	Classic Monograde 50			
Check every 500 km, change every 2500 km				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Classic Multigrade 10W-30	Classic Monograde 30			

TRANSAXLE MANUAL 4/1 Capacity: 1,08 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 5000 km, change every 20000 km	· · · · · · · · · · · · · · · · · · ·

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 5000 km	<u>'</u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.