FIAT (EU) 500 NUOVA NUOVA 500 (1957-1960)



ENGINE Capacity: 1,66 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Monograde 50		
Check every 500 km, change every 25	00 km		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 10W-30	Classic Monograde 30		

TRANSAXLE MANUAL 4/1 Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
Normal PRODUCT RECOMMENDATION 1	Moderate

Check every 5000 km, change every 20000 km

Check every 500 km, change every 2500 km

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 5000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.