FORD EUROPE TAUNUS 15M 15M (1.7 - HC) P6 (1969-1970)



| ENGINE Capacity: 3 liter, Filter capacity: 0,5 lite | er | |
|--|---------------------------|---------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Multigrade 20W-50 | Classic Multigrade 15W-40 | Classic Multigrade 10W-30 |
| Change every 10000 km/ 6 months | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Multigrade 20W-50 | Classic Multigrade 15W-40 | Classic Multigrade 10W-30 |

Change every 1000 km

| TRANSAXLE 4/1 Capacity: 3 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear EP 90 | |
| Change every 20000 km | I |

| HYDRAULIC BRAKE SYSTEM | | | | |
|--------------------------|----------|--|--|--|
| USE | CLIMATE | | | |
| Normal | Moderate | | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Drauliquid DOT 3 | | | | |

| COOLING SYSTEM Capacity: 5,8 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

FORD EUROPE TAUNUS 15M 15M (1.7 - HC) P6 (1969-1970)



| STEERING BOX Capacity: 0,2 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear EP 80 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.