

FORD (USA) MAVERICK MAVERICK 4.9 (302 CI) (1971-1977)



ENGINE 302 ci
Capacity: 4,7 liter, Filter capacity: 0,95 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Change every 10000 km/ 6 months/ 6000 miles

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 3

Classic Monograde 30

Change every 10000 km/ 6 months/ 6000 miles

DIFFERENTIAL REAR

Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

Check every 5000 miles/ 5 months

TRANSMISSION AUTOMATIC C4 3/1

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F

Check every 5000 miles/ 5 months, change every 30000 miles/ 30 months

TRANSMISSION MANUAL

Capacity: 1,66 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

Check every 5000 miles/ 5 months

FORD (USA) MAVERICK MAVERICK 4.9 (302 CI) (1971-1977)



HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 12,8 liter, Capacity: 13,3 liter (+ airconditioning)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -26		

Check every 15000 miles/ 15 months, change every 35 months/ 35000 miles

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.