FORD (USA) TORINO TORINO 5.8 (351W)


(1975-1976)



SE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 5000 miles/ 5 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Multigrade 15W-40	Classic Multigrade 10W-30	Classic Monograde 30
Change every 5000 miles/ 5 months		
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 2500 miles/ 2 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Multigrade 15W-40	Classic Multigrade 10W-30	Classic Monograde 30
Change every 2500 miles/ 2 months		
DIFFERENTIAL REAR Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

DIFFERENTIAL REAR LIMITED SLIP Capacity: 2,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear LS 90	

FORD (USA) TORINO TORINO 5.8 (351W)





TRANSMISSION AUTOMATIC C4 3/1 Capacity: 9,5 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		
Change every 20000 miles/ 20 months		
TRANSMISSION AUTOMATIC C6 3/1 Capacity: 11,5 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1 Classic ATF F		
Change every 20000 miles/ 20 months		
TRANSMISSION AUTOMATIC FMX 3/1		
Capacity: 10,4 liter (Dry fill)		
use Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1		Moderate
Classic ATF F		
use Severe		CLIMATE Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		
Change every 20000 miles/20 menths	<u> </u>	I
Change every 20000 miles/ 20 months		

Normal

PRODUCT RECOMMENDATION 1

Change every 30000 miles/30 months

Classic ATF F



FORD (USA)	ORINO	IORINO	5.8	(351	W)
(1975-1976)					

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 30000 miles/ 30 months			
POWER STEERING			
Capacity: 1,7 liter			
USE		CLIMATE	

Moderate

GREASE POINTS/NIPPLES OTHERS			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 30000 miles/ 30 months	·	

COOLING SYSTEM Capacity: 15 liter, Capacity: 15,3 liter (+ airconditioning)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant -26			

Check every 15000 miles/ 15 months, change every 40000 miles/ 40 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.