

HOLDEN KINGSWOOD HK/HT/HG

KINGSWOOD HK 161 LC (1968-1969)

**ENGINE** 161 LC

Capacity: 4,26 liter, Filter capacity: 0,85 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 10000 km/ 2 months*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 2 months*

| USE | CLIMATE |
|---|---------------|
| Winter months (daytime temperature < 10° C) | Mediterranean |

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 10000 km/ 1 months*

| USE | CLIMATE |
|---|----------|
| Winter months (daytime temperature < 10° C) | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 1 months*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6400 km/ 2 months*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 6400 km/ 2 months*

HOLDEN KINGSWOOD HK/HT/HG

KINGSWOOD HK 161 LC (1968-1969)

**DIFFERENTIAL REAR**

Capacity: 1,42 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,42 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 10000 km***TRANSMISSION AUTOMATIC** GM Powerglide 2/1

Capacity: 5,8 liter (Dry fill), Capacity: 1,82 liter (Service fill)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 10000 km, change every 20000 km***TRANSMISSION MANUAL 3/1**

Capacity: 0,99 liter (Standard), Capacity: 2,56 liter (Synchromesh gearbox)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km, change every 20000 km***TRANSMISSION MANUAL 4/1**

Capacity: 1,14 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km*

HOLDEN KINGSWOOD HK/HT/HG

KINGSWOOD HK 161 LC (1968-1969)



HYDRAULIC BRAKE SYSTEM

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| <i>Check every 10000 km</i> | | |

HYDRAULIC CLUTCH SYSTEM

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 3 | | |
| <i>Check every 10000 km</i> | | |

POWER STEERING

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic ATF A | | |
| <i>Check every 10000 km</i> | | |

GREASE POINTS/NIPPLES GENERAL

| USE | | CLIMATE |
|--|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Change every 20000 km/ 6 months</i> | | |

GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE | | CLIMATE |
|--|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| <i>Change every 20000 km/ 6 months</i> | | |

HOLDEN KINGSWOOD HK/HT/HG

KINGSWOOD HK 161 LC (1968-1969)

**COOLING SYSTEM**

Capacity: 9,1 liter, Capacity: 8,86 liter (with automatic transmission)

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.