

HOLDEN MONARO HK/HT/HG MONARO

GTS 350 HG 350 LC (1970-1971)

**ENGINE** 350 LC

Capacity: 4,55 liter, Filter capacity: 0,85 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 10000 km/ 2 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 2 months*

USE	CLIMATE
Winter months (daytime temperature < 10° C)	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 10000 km/ 1 months*

USE	CLIMATE
Winter months (daytime temperature < 10° C)	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 10000 km/ 1 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 6400 km/ 2 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 2

Classic Multigrade 10W-30*Change every 6400 km/ 2 months*

HOLDEN MONARO HK/HT/HG MONARO

GTS 350 HG 350 LC (1970-1971)

**DIFFERENTIAL REAR GMH**

Capacity: 1,42 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,42-1,88 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 10000 km***DIFFERENTIAL. REAR Salisbury**

Capacity: 1,88 liter (Heavy Duty), Capacity: 1,65 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km***TRANSMISSION AUTOMATIC GM Powerglide 2/1**

Capacity: 8,64 liter (Dry fill), Capacity: 2,27 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 10000 km, change every 20000 km***TRANSMISSION AUTOMATIC Trimatic 3/1**

Capacity: 8,7 liter (Dry fill), Capacity: 2,27 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 10000 km, change every 20000 km*

HOLDEN MONARO HK/HT/HG MONARO

GTS 350 HG 350 LC (1970-1971)



TRANSMISSION MANUAL 4/1

Capacity: 1,62 liter (Heavy Duty), Capacity: 1,14 liter (Standard)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km*

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 10000 km*

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 10000 km*

GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 20000 km/ 6 months*

HOLDEN MONARO HK/HT/HG MONARO GTS 350 HG 350 LC (1970-1971)



GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 20000 km/ 6 months

COOLING SYSTEM

Capacity: 9,1 liter, Capacity: 8,86 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.