

JAGUAR (EU) XJ XJ6 3.4 SERIES 2 (1975-1979)



ENGINE XK-I6
Capacity: 8,3 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50

Change every 10000 km/ 6 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40

Change every 10000 km/ 6 months

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

Change every 10000 km/ 6 months

DIFFERENTIAL REAR

Capacity: 1,55 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 5000 km, change every 10000 km

DIFFERENTIAL REAR LIMITED SLIP Powr-Lok

Capacity: 1,55 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90

Check every 5000 km, change every 10000 km

JAGUAR (EU) XJ XJ6 3.4 SERIES 2 (1975-1979)



TRANSMISSION AUTOMATIC

Capacity: 7,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		

TRANSMISSION MANUAL 4/1

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		

COOLING SYSTEM

Capacity: 18,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.