JAGUAR (EU) XK SERIES XK 150 3.8 (1959-1961)



ENGINE XK-I6 Capacity: 8,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 4000 km		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Change every 4000 km		

DIFFERENTIAL REAR Capacity: 1,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	
Check every 4000 km, change every 16000 km	·

TRANSMISSION MANUAL 4/1 Capacity: 1,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 10W-30	Classic Monograde 30		

Check every 4000 km, change every 16000 km	
--	--

TRANSMISSION MANUAL WITH OVE Capacity: 2,25 liter	ERDRIVE 4/1		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 10W-30	Classic Monograde 30		
Check every 4000 km, change every 1	6000 km	,	

JAGUAR (EU) XK SERIES XK 150 3.8 (1959-1961)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 1 week	·	

GREASE POINTS/NIPPLES			
	CLIMATE		
	Moderate		
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 13 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.