

JEEP CJ CJ-5 BUICK 3,7 DAUNTLESS (1965-1971)

**ENGINE** Buick 225

Capacity: 4,8 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Change every 3000 km/ 2 months***DIFFERENTIAL FRONT**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1600 km, change every 16000 km***DIFFERENTIAL REAR**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1600 km, change every 16000 km***TRANSFERBOX**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 1600 km, change every 16000 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 1600 km, change every 16000 km*

JEEP CJ CJ-5 BUICK 3,7 DAUNTLESS (1965-1971)



TRANSMISSION MANUAL 4/1

Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 1600 km, change every 16000 km

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 1600 km, change every 16000 km

TRANSMISSION MANUAL + TRANSFER CASE 3/1

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 1600 km, change every 16000 km

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 1600 km, change every 16000 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

JEEP CJ CJ-5 BUICK 3,7 DAUNTLESS (1965-1971)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Check every 1600 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 0*Check every 1600 km*

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

STEERING GEARBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 1600 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.