

JEEP WAGONEER SJ WAGONEER V8 360

(1974-1979)



ENGINE 360
Capacity: 4,7 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Check every 1000 km, change every 8000 km/ 5 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 3

Classic Multigrade 10W-30

Check every 1000 km, change every 8000 km/ 5 months

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

HDX 10W

Check every 1000 km, change every 8000 km/ 5 months

USE
Severe

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Check every 1000 km, change every 5000 km/ 3 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 3

Classic Multigrade 10W-30

Check every 1000 km, change every 5000 km/ 3 months

USE
Severe

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1

HDX 10W

Check every 1000 km, change every 5000 km/ 3 months

JEEP WAGONEER SJ WAGONEER V8 360

(1974-1979)

**DIFFERENTIAL FRONT** Dana 44

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 8000 km, change every 48000 km***DIFFERENTIAL REAR** Dana 44

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 8000 km, change every 48000 km***TRANSFERBOX** Dana 20

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 8000 km, change every 48000 km***TRANSMISSION MANUAL** T-18/T-18a 4/1

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 8000 km, change every 48000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 8000 km*

JEEP WAGONEER SJ WAGONEER V8 360

(1974-1979)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	Classic ATF A	

Check every 8000 km

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 24000 km

COOLING SYSTEM

Capacity: 12,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 40000 km/ 25 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.