

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER 2.4 TD (1986-1989)

**ENGINE**

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Change every 10000 km/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

*Change every 5000 km/ 1 months***DIFFERENTIAL FRONT**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER 2.4 TD (1986-1989)

**TRANSFERBOX LT230T**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***TRANSMISSION MANUAL LT77 5/1**

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km/ 6 months, change every 40000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 30000 km/ 18 months***HYDRAULIC CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER 2.4 TD (1986-1989)



POWER STEERING

Capacity: 2,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 20000 km/ 12 months

GREASE POINTS/NIPPLES SWIVEL PIN HOUSINGS

Capacity: 0,35 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

COOLING SYSTEM

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.