

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER V8-3.9l (1989-1994)

**ENGINE** Rover V8 3.9/4.0

Capacity: 6,6 liter (Initial fill), Capacity: 6,25 liter (Service fill)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Classic Racing Oil 15W-50

Change every 20000 km/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Change every 20000 km/ 12 months

USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Classic Racing Oil 15W-50

Change every 5000 km/ 100 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

*Change every 5000 km/ 100 hours***DIFFERENTIAL FRONT**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER V8-3.9i (1989-1994)

**DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Gear MP 90	Classic Gear EP 80	Gearlube RPC 75W-80

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSFERBOX Borg Warner

Capacity: 2,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION AUTOMATIC 4/1

Capacity: 9,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF Almirol	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION MANUAL LT77 5/1

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER V8-3.9i (1989-1994)



HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 30000 km/ 18 months*

HYDRAULIC CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

POWER STEERING

Capacity: 2,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

GREASE POINTS/NIPPLES OTHERS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 20000 km/ 12 months*

LAND ROVER (EU) RANGE ROVER (CLASSIC) RANGE ROVER V8-3.9l (1989-1994)



GREASE POINTS/NIPPLES SWIVEL PIN HOUSINGS

Capacity: 0,35 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90

PRODUCT RECOMMENDATION 2

Classic Gear EP 80

PRODUCT RECOMMENDATION 3

Gearlube RPC 75W-80

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

COOLING SYSTEM

Capacity: 11,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

Change every 40000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.