

MERCEDES-BENZ (EU) 114 / 115 SERIES

W114 / 115 (/8) 220D 115.110 (1968-1976)

**ENGINE OM615**

Capacity: 4 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 5000 km*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Change every 5000 km*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 5000 km***DIFFERENTIAL REAR**

Capacity: 1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 20000 km***TRANSMISSION AUTOMATIC 4/1**

Capacity: 4,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 5000 km, change every 50000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 5000 km, change every 25000 km*

MERCEDES-BENZ (EU) 114 / 115 SERIES

W114 / 115 (/8) 220D 115.110 (1968-1976)

**TRANSMISSION MANUAL 4/1**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Change every 20000 km***HYDRAULIC LEVELLING SYSTEM**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023*Check every 5000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 5000 km, change every 24 months***POWER STEERING**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 5000 km, change every 50000 km***COOLING SYSTEM**

Capacity: 10,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

MERCEDES-BENZ (EU) 114 / 115 SERIES

W114 / 115 (/8) 220D 115.110 (1968-1976)

**STEERING BOX**

Capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Gear MP 90***Check every 20000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.