

MERCEDES-BENZ (EU) 123 SERIES W123

300CD TURBODIESEL 123.153 (1981-1985)

**ENGINE** OM617.952

Capacity: 9,5 liter (Dry fill), Capacity: 7,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 20W-50	Bi-Turbo 15W-40

Check every 500 km, change every 7500 km/ 6 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

Check every 500 km, change every 7500 km/ 6 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 20W-50	Bi-Turbo 15W-40

Change every 3500 km

USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

*Change every 3500 km***DIFFERENTIAL REAR**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 15000 km/ 12 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Change every 7500 km

MERCEDES-BENZ (EU) 123 SERIES W123

300CD TURBODIESEL 123.153 (1981-1985)

**TRANSMISSION AUTOMATIC 722.3xx 4/1**

Capacity: 7,3 liter (Dry fill), Capacity: 6,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 1500 km/ 12 months, change every 45000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Change every 22500 km***HYDRAULIC LEVELLING SYSTEM**

Capacity: 4,2 liter (Metal reservoir), Capacity: 3,5 liter (Plastic sump)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023*Check every 15000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Check every 500 km, change every 12 months***POWER STEERING**

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF A*Check every 15000 km/ 12 months*

MERCEDES-BENZ (EU) 123 SERIES W123

300CD TURBODIESEL 123.153 (1981-1985)

**COOLING SYSTEM**

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 500 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.