

MERCEDES-BENZ (EU) SL / SLC R107 / C107 500 SL 107.046 (1986-1989)

**ENGINE M117.E50**

Capacity: 8 liter, Filter capacity: 1,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Change every 5000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90

PRODUCT RECOMMENDATION 2

Classic Gear MP 90*Check every 20000 km, change every 10000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 20000 km, change every 10000 km*

MERCEDES-BENZ (EU) SL / SLC R107 / C107 500 SL 107.046 (1986-1989)



TRANSMISSION AUTOMATIC 722.3xx 4/1

Capacity: 7,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
ATF Dexron II-D	ATF Almirol

Check every 20000 km, change every 60000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
ATF Dexron II-D	ATF Almirol

Check every 20000 km, change every 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

Check every 20000 km, change every 12 months

POWER STEERING

Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic ATF A	

Check every 20000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Labora Grease	

Check every 20000 km

MERCEDES-BENZ (EU) SL / SLC R107 / C107 500 SL 107.046 (1986-1989)

**COOLING SYSTEM**

Capacity: 13,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 20000 km, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.