MG MIDGET MIDGET MK III 1500 (1974-1977)



ENGINE Capacity: 4,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Change every 10000 km/ 6 months		
DIFFERENTIAL REAR Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

USE	CLIMATE
top up	Arctic
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

Check every 10000 km/6 months

Check every 10000 km/6 months

TRANSMISSION MANUAL 4/1 Capacity: 0,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	
Check every 10000 km/ 6 months	·

MG MIDGET MIDGET MK III 1500 (1974-1977)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Check every 10000 km/ 6 months	

HYDRAULIC CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
Check every 10000 km/ 6 months	'	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease Q5 MP Calcep Grease EP 2		MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 4,25 liter (+ heater)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -26	
Check every 10000 km/ 6 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.