## MITSUBISHI (EU) LANCER LANCER 1400 A72 (1973-1979)



<b>ENGINE</b> 4G33 Capacity: 4 liter, Filter capacity: 0,5 lite	r	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 20W-50		
Change every 5000 km		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	Classic Multigrade 10W-30
Change every 5000 km		

DIFFERENTIAL REAR Capacity: 1,1 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

TRANSMISSION MANUAL 4/1 Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

TRANSMISSION MANUAL 5/1 Capacity: 2,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

## MITSUBISHI (EU) LANCER LANCER 1400 A72 (1973-1979)



HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Grease EP 0	Gear Grease EP 00/000		

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 40000 km/ 24 months	'

STEERING BOX Capacity: 0,18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.