MORRIS 1800/2200 ADO17 1800 MK III (1973-1975)

KROON OIL

ENGINE/TRANSAXLE MANUAL Capacity: 8,5 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			_
Classic Multigrade 20W-50			
Change every 10000 km/ 6 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Multigrade 15W-40	Classic Multigrade 10W-30		

Change every 10000 km/ 6 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

МАТЕ
oderate
d

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic ATF F	
Check every 10000 km/ 6 months	

MORRIS 1800/2200 ADO17 1800 MK III (1973-1975)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 5,2 liter (+ heater), Capacity: 4,8 liter (Without heater)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CARBURETTOR DAMPER	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Multigrade 20W-50	

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Classic Multigrade 15W-40	PRODUCT RECOMMENDATION 2 Classic Multigrade 10W-30	

Check every 10000 km/ 6 months, change every 30000 km/ 18 months

STEERING BOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.