MORRIS MINOR MINOR SERIES II (1953-1956)



ENGINE Capacity: 3,8 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 4800 km	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Oh - 19 - 19 - 19 - 19 - 19 - 19 - 19 - 1	

Change every 4800 km

DIFFERENTIAL REAR Capacity: 0,85 liter		
USE	CLIM	ATE
Normal	Мо	derate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Check every 1600 km, change every 9600 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	
Check every 1600 km, change every 9600 km		

TRANSMISSION MANUAL 4/1 Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Check even (1600 km chenne even (1600 km		

Check every 1600 km, change every 9600 km

MORRIS MINOR MINOR SERIES II (1953-1956)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 1600 km

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
01 1 10001		

Check every 1600 km

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 9600 km

COOLING SYSTEM Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

MORRIS MINOR MINOR SERIES II (1953-1956)



STEERING BOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		
Check every 19200 km		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube RPC 75W-80	SP Gear 5015	
Check every 19200 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.