## OPEL MANTA B MANTA 1.3 (1983-1988)



| ENGINE 13S, 13SC<br>Capacity: 2,5 liter, Filter capacity: 0,3 liter |  |               |
|---|--|---------------|
| USE   |  | CLIMATE       |
| Normal  |  | Mediterranean |
| PRODUCT RECOMMENDATION 1  |  |               |
| Bi-Turbo 20W-50   |  |               |
| Check every 500 km, change every 15000 km/ 6 months                 |  |               |
| USE   |  | CLIMATE       |

| Normal                   |                          | Moderate                 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Asyntho 5W-30            | Emperol 10W-40           | Bi-Turbo 15W-40          |

Check every 500 km, change every 15000 km/ 6 months

| DIFFERENTIAL REAR<br>Capacity: 1,1 liter |          |
|--|----------|
| USE                                      | CLIMATE  |
| Normal                                   | Moderate |
| PRODUCT RECOMMENDATION 1                 |          |
| Classic Gear MP 90                       |          |
| Check every 12 months                    |          |

| TRANSMISSION AUTOMATIC 3/1<br>Capacity: 2 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal  | Moderate |
| PRODUCT RECOMMENDATION 1                        |          |
| ATF Dexron II-D                                 |          |
| 01 00 11  |          |

Change every 36 months

| TRANSMISSION MANUAL 4/1<br>Capacity: 1,1 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Classic Gear EP 80                             |          |
| 01 1 10 11                                     |          |

Check every 12 months

## **OPEL MANTA B MANTA 1.3** (1983-1988)



| HYDRAULIC BRAKE SYSTEM<br>Capacity: 0,4 liter |                    |
|---|--------------------|
| use<br>Normal                                 | сымате<br>Moderate |
| PRODUCT RECOMMENDATION 1 Drauliquid-S DOT 4   |                    |
|   |                    |

Check every 500 km, change every 12 months

| COOLING SYSTEM<br>Capacity: 5,8 liter      |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal                                     |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant -38 Organic NF                     | Coolant -26              |          |  |
| Check every 500 km, change every 24 months |                          |          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.