

## OPEL REKORD REKORD 1.9 (1972-1977)



**ENGINE 19S**  
Capacity: 3,8 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Classic Monograde 30**

*Change every 5000 km/ 3 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Multigrade 10W-30**

*Change every 5000 km/ 3 months*

**DIFFERENTIAL REAR**  
Capacity: 1,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Gear MP 90**

*Check every 10000 km/ 6 months*

**TRANSMISSION AUTOMATIC 3/1**  
Capacity: 2,5 liter (Refill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic ATF A**

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

**TRANSMISSION MANUAL 4/1**  
Capacity: 1,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Gear MP 90**

*Check every 10000 km/ 6 months*

**OPEL REKORD REKORD 1.9 (1972-1977)****HYDRAULIC BRAKE SYSTEM**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

*Check every 5000 km*

**COOLING SYSTEM**

Capacity: 7,1-7,2 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

**STEERING BOX**

Capacity: 0,3 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Classic Gear EP 90</b> |  |          |

*Check every 10000 km/ 6 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*