PORSCHE (EU) 356 356A 1600 (1955-1959)



| ENGINE Capacity: 3 liter, Filter capacity: 1 liter | | | | |
|--|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Classic Multigrade 10W-30 | Classic Monograde 30 | | | |
| Chairman average E000 km/ Comparished | | · | | |

Change every 5000 km/6 months

| TRANSAXLE MANUAL 4/1 Capacity: 3,5 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear MP 90 | |
| Change every 10000 km/ 6 months | · |

| HYDRAULIC BRAKE SYSTEM | | | |
|--------------------------|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Drauliquid DOT 3 | | | |

| GREASE POINTS/NIPPLES WHEEL BEARINGS Capacity: 50 grams (each side) | | | | |
|---|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.