

RELIANT SCIMITAR SE/SS SCIMITAR GT 2.5 SE4A/B (1967-1970)



ENGINE Ford Essex
Capacity: 4,54 liter, Filter capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 10W-30	Classic Monograde 30

Change every 5000 km/ 3 months

REAR AXLE
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Change every 8000 km

TRANSMISSION MANUAL 4/1
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

Check every 8000 km

USE	CLIMATE
Initial service (no changing needed anymore)	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear EP 80	

Change every 8000 km

RELIANT SCIMITAR SE/SS SCIMITAR GT 2.5 SE4A/B (1967-1970)



TRANSMISSION MANUAL + OVERDRIVE 5/1

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 8000 km*

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

RELIANT SCIMITAR SE/SS SCIMITAR GT 2.5 SE4A/B (1967-1970)

**COOLING SYSTEM**

Capacity: 12,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.