## RENAULT (EU) 12 12 1.3 L, TL 1170, 1330



(1969-1980)

ENGINE 810-02 Capacity: 3,25 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Racing Oil 15W-50	Classic Multigrade 15W-40	
Change every 10000 km/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Change every 10000 km/ 12 months		

TRANSAXLE AUTOMATIC 3/1 Capacity: 5 liter (Dry fill), Capacity: 2-	2,5 liter (Service fill)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			

Check every 15000 km/12 months, change every 30000 km/24 months

TRANSAXLE MANUAL 4/1 Capacity: 2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube RPC 75W-80	SP Gear 5015		
01	-		

Change every 15000 km/ 12 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	<b>.</b>
Normal	Mode	rate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 30000 km/24 months		

## RENAULT (EU) 12 12 1.3 L, TL 1170, 1330





COOLING SYSTEM Capacity: 5-5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 50000 km/ 36 months	·	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.