PRODUCT RECOMMENDATION RENAULT (EU) 6 6 (1.0) R 1183 (1968-1980)



| ENGINE | | |
|----------------------------------|---------------------------|---------------------------|
| Capacity: 2,5 liter | | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Racing Oil 15W-50 | Classic Multigrade 20W-50 | Classic Multigrade 15W-40 |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Multigrade 10W-30 | | |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Racing Oil 15W-50 | Classic Multigrade 20W-50 | Classic Multigrade 15W-40 |
| Change every 500 hours | | |
| USE | | CLIMATE |
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Multigrade 10W-30 | | |
| Change every 500 hours | | |
| | | |
| TRANSAXLE MANUAL 4/1 | | |
| Capacity: 1,8 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear EP 80 | | |
| Change every 15000 km/ 12 months | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear EP 80 | | |
| Change every 500 hours | | |

RENAULT (EU) 6 6 (1.0) R 1183 (1968-1980)



| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|--|--|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Drauliquid DOT 3 | | | | |

| COOLING SYSTEM Capacity: 6,3 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Change every 36 months/ 45000 hours | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.