RENAULT (EU) CARAVELLE / FLORIDE CARAVELLE / FLORIDE (1964-1968)



| ENGINE Capacity: 2,5 liter | |
|-------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Multigrade 15W-40 | |
| Change every 5000 km | |
| USE | CLIMATE |
| Normal | Cold |
| PRODUCT RECOMMENDATION 1 | |
| Classic Multigrade 10W-30 | |
| Change every 5000 km | |

| TRANSAXLE MANUAL 4/1 Capacity: 1,6-1,9 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear EP 80 | |
| Check every 5000 km, change every 10000 km | |

| HYDRAULIC BRAKE SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |

| GREASE POINTS/NIPPLES WHEEL BEARINGS | | |
|--------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

RENAULT (EU) CARAVELLE / FLORIDE CARAVELLE / FLORIDE (1964-1968)



| COOLING SYSTEM Capacity: 4,6 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

| STEERING BOX | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.