

ROVER P4 75 (1949-1954)



ENGINE IOE
Capacity: 8,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Classic Monograde 50

Change every 5000 km

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 10W-30

Change every 5000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 30

Change every 5000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W

Change every 5000 km

DIFFERENTIAL REAR
Capacity: 1,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear EP 90

Check every 1500 km, change every 5000 km

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80

Check every 1500 km, change every 5000 km

ROVER P4 75 (1949-1954)**TRANSMISSION MANUAL 4/1**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Check every 1500 km, change every 5000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 1500 km, change every 5000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 1500 km***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 5000 km***GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 5000 km*

ROVER P4 75 (1949-1954)**COOLING SYSTEM**

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP 460		

Check every 1500 km

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 1500 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.