

SIMCA 1100 1100 7CV (1974-1979)**ENGINE**

Capacity: 3,3 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40

*Change every 5000 km***DIFFERENTIAL FRONT MANUAL TRANSMISSION**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

*Check every 5000 km, change every 10000 km***DIFFERENTIAL FRONT SEMI-AUTOMATIC TRANSMISSION**

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

*Check every 5000 km, change every 10000 km***TRANSMISSION MANUAL 4/1**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

*Check every 5000 km, change every 10000 km***TRANSMISSION SEMI-AUTOMATIC 3/1**

Capacity: 0,5 liter, Capacity: 4,3 liter (Torque converter)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 5000 km

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 km, change every 20000 km/ 12 months

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 20000 km/ 12 months

COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 5000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.