

**SKODA 1200 SERIES 1200 955 (1952-1956)****ENGINE**

Capacity: 3,5 kg

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Classic Monograde 50***Change every 2000 km***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Classic Monograde 30***Change every 2000 km***DIFFERENTIAL REAR**

Capacity: 1,8 kg

**USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Classic Gear EP 90***Check every 2000 km, change every 4000 km***TRANSMISSION 4/1**

Capacity: 1,2 kg

**USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Classic Gear EP 90***Check every 2000 km, change every 4000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,75 kg

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid DOT 3**

**CENTRAL LUBRICATION SYSTEM**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Classic Monograde 50***Change every 100 km*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Classic Monograde 30***Change every 100 km***GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 4000 km***COOLING SYSTEM**

Capacity: 6,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26****STEERING BOX**

Capacity: 0,25 kg

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

PRODUCT RECOMMENDATION 1

**Classic Gear EP 90***Change every 4000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.