

SKODA 440/445/450 440 SPARTAK 970 (1955-1959)

**ENGINE**

Capacity: 2,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Classic Monograde 50*Change every 2000 km*

USE

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Classic Monograde 30*Change every 2000 km***DIFFERENTIAL REAR**

Capacity: 1,4 liter

USE

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 2000 km, change every 4000 km***TRANSMISSION 4/1**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Cold

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 2000 km, change every 4000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

SKODA 440/445/450 440 SPARTAK 970 (1955-1959)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 1500 km

WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 4000 km

WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Change every 1500 km

COOLING SYSTEM

Capacity: 6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX

Capacity: 0,25 liter

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 2000 km, change every 4000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.