SKODA OCTAVIA OCTAVIA COMBI 704

(1969-1972)



ENGINE Capacity: 2,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 2000 km

DIFFERENTIAL REAR Capacity: 1,4 liter	
USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
011	

Check every 2000 km, change every 8000 km

TRANSMISSION 4/1 Capacity: 0,7 liter		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Charles aver 2000 less abanes aver 6	2021	•

Check every 2000 km, change every 8000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease Q5 MP Calcep Grease EP 2		MP Lithep Grease EP 2	

SKODA OCTAVIA OCTAVIA COMBI 704

(1969-1972)



WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 8000 km		

WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 16000 km	'	

COOLING SYSTEM Capacity: 6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

STEERING BOX Capacity: 0,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	

Check every 2000 km, change every 8000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.